

SX-BS-6709



BARCODE SCANNER with BLUETOOTH



SX-BS-6709 is industrial-grade bar code scanner. By enhancing the technology,with the best scanning light source now can read some bad-qualified ,damaged and dirty bar code .It is characterized by stable performance and durability. With industrial housing protection,even in noisy and industrial environment, high volume buzzer can meet the requirement on confirming each scanning.

FEATURES

- Bluetooth connection.
- Upto IP54 industrial level, waterproof, dustproof.
- Manual trigger/continuous scan/auto-sense(for choice),very comfortable operating.
- Quick decoding capability with duddy fuzzy information processing system.
- Support remote software update.
- Upto 10,000 hours laser life , french press key with life of 3 million pressing times.
- Support multi-interface: RS232/USB/KB.
- Ergonomic design offer comfortable operation and enhance the working efficiency.



SX-BS-6709



SPECIFICATIONS

| Model | SX-BS-6709 |
|-----------------------|--|
| Type of illuminant | 650-670 nm (visible laser) |
| Scan rate | 100 scan s/second |
| Reading preciseness | 0.10 mm (4mil) |
| Interface | PS2, RS232, USB and more |
| Depth of field | 0-600 mm (0.33mm PCS 90%) |
| Reading distance | 2.5-600 mm (100%UPC/EAN) |
| Print contrast | 30% min |
| Barcode types | EAN-8/13, UPC-A/E, code 39/93/128, EAN 128, Codabar industrail 2 of 5, interleave 2 of 5, matriz 2 of 5, MSI |
| EEPROM | 512 KB storage for barcodes |
| Scan scope | 10 mm - 250 mm |
| Scanning angle | Inclination angle 55°, elevation angle 60° |
| Bit error rate | 1/5 million |
| Fall test | 1.8 m |
| Power voltage | 5v |
| Working current | 85mA |
| Static current | 36mA |
| Safety performance | Accord with national level 2 laser safety standards |
| Dimension | 165 mm * 63 mm * 87 mm |
| Weight | 129g |
| Material | ABS+PC |
| Operating temperature | 0°C-45°C |
| Storage temperature | -20°C-60°C |
| Humidity | 5% - 95% |
| Color | White / Black |

PRODUCT APPEARANCE

